











PORTABLE DATA COLLECTOR

FEATURES

Rugged Construction

The NLS-MT65's rugged housing is sealed to IP65 standards for protection against dust and water and withstands 1.2m drops to concrete.

O Superior Barcode Reading Performance

When equipped with Newland's fifth-generation **LIMG**® technology, the new NLS-MT65 can decode even poorer quality barcodes, such as soiled or wrinkled labels, with ease

O Heavily Customized Android

The value-added features of the NLS-MT65, including application protection and admin tool, seek to shore up Android's data security.

O Diverse Functionalities

The NLS-MT65 offers ID/2D/BT/Wi-Fi/4G/3G /GPS/Camera/NFC functionalities to meet various application needs.

















IF

NLS-MT65

		,			
- 2	or	\mathbf{c}	rm	n	0

Processor 2.0GHz quad-core processor

Operating System Android 11

Memory 3GB RAM, 32GB ROM

Interface Micro USB 2.0, Battery charging over USB supported

Physical/Electrical

Dimensions (L×W×H) 166 ×73 ×26 mm

Weight 330g (including battery)

 Display
 4"WVGA (800×480) capacitive touch screen

 Keypad
 30 keys (side keys included) with backlight

 Notification
 Vibration, speaker and multi-color LEDs

Battery 3.7V, 3800mAh

Camera 8 megapixels, auto focus, with LED flashlight

GPS GPS (AGPS), GLONASS
Expansion Micro SD card (max. 128GB) slot

AC Adapter Output: DC5V, 2.0A Input: AC100~240V, 50~60Hz

Environmental

Operating Temperature -20°C to 50°C (-4°F to 122°F)

Storage Temperature -30°C to 70°C (-22°F to 158°F)

Humidity 5% to 95% (non-condensing)

Static Discharge ±15 kV (air discharge), ±8 kV (direct discharge)

Drop 1.2m drops to concrete (for six sides, one drop per side)

Sealing IP65

Barcode Scanning

2D Scan Engine Laser aiming Mega-pixel 1D: Code128, Code 49, Code 16K, (GS1128) UCC/EAN-128, AIM-128, EAN-8, EAN-13, UPC-E, UPC-

A, ITF, ITF 6, ITF 14, Matrix 2 of 5, Industrial 25, Standard 2 of 5, Code39, ISSN, ISBN, Codabar,

Code93, Code 11, Plessey, MSI Plessey, RSS.

2D: Aztec, Composite, CS Code, Maxicode, Micro PDF, Micro QR, PDF 417, QR Code, Data

Matrix, DotCode.

Depth of Field

Depends on barcode type and environment Code39 (20mil) 90mm-580mm; EAN13 (13mil) 45mm-380mm

Code39 (5mil) 75mm-180mm; DM (10mil) 50mm-180mm PDF417 (6.7mil) 70mm-170mm; QR (15mil) 40mm-220mm

NFC

13.56MHz RFID ISO14443A/B, MIFARE, FeliCa, NFC Forum Tags, ISO15693

Wireless

WPAN RADIO

WLAN RADIO IEEE 802.11 a/b/q/n/ac, 2.4GHz and 5GHz

WWAN RADIO 2G GSM (B2, B3, B5, B8)

3G WCDMA (B1, B2, B5, B8); CDMA2000 1X/ EV-DO Rev. A (BC0); TD-SCDMA (B34, B39)

4G TD-LTE (B38, B39, B40, B41)

FDD-LTE (B1, B2, B3, B5, B7, B8, B20, B28 a&b)

Dual mode Bluetooth 5.0+BLE (Backward-compatible)

Optional Accessories

AC adapter, cable, charging cradle, 4-slot charger

Specifications are subject to change without notice.

2021/12/27

Version: V1.0

Newland AIDC

Add: No.1 Rujiang West Rd.,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax +86-591-83979216
Email: info@nlscan.com
Web: www.newlandaidc.com

North America&Latin America Add: 46559 Fremont Blvd.,

Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@nlscan.com
Web: www.newlandamerica.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com
Web: www.newland-id.com

Asia Pacific

Taiwan:

Add: 7F-6, No. 268, Liancheng Rd., Jhonghe Dist. 235, New Taipei City,Taiwan Tel: +886 2 7731 5388 Email: info@newland-id.com.tw

