



NLS-WD1

WEARABLE DATA COLLECTOR

FEATURES

- **Rugged Construction**
The NLS-WD1's rugged housing is sealed to IP67 standards for protection against dust and water and withstands 1.2m drops to concrete.
- **User-focused Ergonomics**
The slim ergonomically designed body of the NLS-WD1 makes it easy to wear it in your hand and reduces stress & fatigue during extended work sessions.
- **Diverse Wearable Solutions**
The NLS-WD1 can be connected to various Bluetooth peripherals to meet application needs like barcode scanning, UHF, print, etc. All these expand the working ability of the smart watch.
- **High-precision Sensor**
Armed with multiple sets of high-precision sensors, the NLS-WD1 can position the user's location and speed in real time.
- **Long-lasting Battery Life**
The NLS-WD1 is equipped with a 3300mAh battery that provides a full-shift battery life of up to 12 hours from a single charge.
- **Heavily Customized Android**
Heavily customized android operation system allows users to easily operate and execute applications.
- **Excellent Performance**
The NLS-WD1 is equipped with quad-core high-performance processor, 3+32GB memory, providing faster and smoother performance all the time.
- **Corning Glass**
The dial plate adopts rugged corning glass which can provide high resistance to scratch and improve the drop performance.



Android



USB Type C



Drop



GPS



WiFi
Dual Band



Bluetooth

NLS-WD1

Performance

Processor	2.0 GHz, octa cores 64-bit processor
Operating System	Android 13
Memory	3GB RAM, 32GB ROM
Interface	USB Type -C, battery charging over USB supported, OTG not supported

Physical/Electrical

Dimensions (L×W×H)	Dial plate: 77 × 56 (mm), the thickness of the dial plate: 17.8mm
Weight	143g
Display	2.8" (640 × 480) capacitive touch screen, corning glass for the dial plate
Keypad	2keys (power key/lock screen key, user-defined key)
Notification	Vibrator, speaker, and LED
Battery	3.8V, 3300mAh (non-removable)
Camera	13 megapixels, auto focus; LED Flash, support torch mode
GPS	GPS (AGPS), GLONASS, Beidou, Galileo
Media	Speaker *1, dual microphone, noise reduction
Sensor	Angular Velocity Sensor, Geomagnetic Sensor, Air Pressure Sensor, Acceleration Sensor

Environmental

Operating Temperature	-20℃ to 55℃ (-4°F to 131°F)
Storage Temperature	-30℃ to 70℃ (-22°F to 158°F)
Humidity	5% to 95% (non-condensing)
Static Discharge	±10 kV (Air discharge), ±6 kV (Direct discharge)
Drop	1.2m drops to concrete (for six sides, one drop per side)
Sealing	IP67

Wireless

WLAN RADIO	Bands	built-in 802.11 a/b/g/n/ac,, support 2.4G and 5G dual frequency
WPAN RADIO		Bluetooth 5.0

Accessory

AC adapter, cable, Cradle

Specifications are subject to change without notice.

2024/03/28

Version: V1.0

Newland AIDC

Add: No.1 Rujiang West Rd,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@nlscan.com
Web: www.newlandaidc.com

Asia Pacific

Taiwan:
Add: 7F-6, No. 268, Liancheng Rd.,
Jhonghe Dist. 235, New Taipei City, Taiwan
Tel: +886 2 7731 5388
Email: info@newland-id.com.tw

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com

North America & Latin America

Add: 46559 Fremont Blvd.,
Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@nlscan.com